

AP-545V SPECIFICATION SHEET

Part Number	AP-545V000-000	Model No.	AP-545V	Doc. No.	B40-P1105-00
1st Issued Date	01 / 05 / 98	Revised Date	11 / 5 / 99	Revised No.	03
Model Description : Half-size CPU Card with VGA and Flash Disk for ZIF Socket 7 Processor					
<p>Processor : Intel Pentium P54C/P55C, AMD K5/K6, Cyrix 6x86 M1/M2</p> <p>Chipset : SIS 5598 chipset, and Winbond 977TF chipset</p> <p>System Memory / RAM : One DIMM socket, support up to 128MB SDRAM</p> <p>Cache Memory : 512KB pipeline burst secondary cache</p> <p>BIOS : 256KB AMI license BIOS</p> <p>Flash Memory Disk : Reserved socket for DiskOnChip from M-System , support up to 144 MB flash memory disk</p> <p>VGA Controller : VGA on chipset SIS 5598 support up to 4 MB shared memory</p> <p>IDE Drive Interface : One PCI IDE port , support up to two IDE devices and Ultra DMA-33</p> <p>Floppy Drive Interface : One FDD port , support up to two floppy devices</p> <p>Serial Port : Two COM ports , one RS-232 and one RS-232 / 422 / 485</p> <p>Parallel Port : One multi-mode parallel port (SPP/EPP/ECP)</p> <p>Bus Interface : ISA bus</p> <p>RTC Battery : Dallas RTC battery</p> <p>DMA : 8 DMA channels</p> <p>Interrupts : 16 levels of hardware interrupts</p> <p>PS/2 Mouse Connector : On-board 6-pin Mini-Din PS/2 mouse connector</p> <p>Keyboard Connector : On-board 5-pin header and 6-pin Mini-Din connectors</p> <p>Expansion Bus : Lanner PCI piggyback expansion bus</p> <p>Watchdog Timer : 8 level time-out intervals (0.5 / 1 / 2 / 4 / 8 / 16 / 32 / 64 sec.)</p> <p>Universal Serial Bus : Support 2 USB ports</p> <p>IR Interface : Support one IrDA header</p> <p>Operating Temperature : 5°C ~ 50°C</p> <p>Humidity : 10% ~ 90% RH</p> <p>Dimensions : 185 x 122 mm (7 1/4" x 4 5/6" inches)</p> <p>Net weight : 250 g (0.517 pounds)</p>					

Lanner Electronics Inc.

TEL : 886-2-26981828 FAX : 886-2-26981107

8F-4, NO.77, Sec.1, Hsin Tai Wu Rd., Hsi-Chih, Taipei Hsien, Taiwan R.O.C.

E-Mail : sales@lannerinc.com w.w.w. : www.lannerinc.com